

Reliable Solution for Data Centre BN500. IT Basic Series

BACHMANN provides a huge choice of PDUs in a high-quality aluminium profile.





Why Choose BACHMANN PDUs?

	CORE FEATURES	DESCRIPTION	BENEFIT
Customize Ordering	BACHMANN Customisation Modular	 A wide range of country-specific outlet ports, protection options such as modular surge protection Tailor-made units that extend beyond the standard product range (socket type, quantity, angle) Enable small quantities ordering 	Your needs will be fully considered
Optimize Energy Cost	Energy Monitoring and Management*	Measurement by meter	Energy meter can be reset (Value is stored even if there is no power supply)
Identifying Power Supply	Colour Coding	 To quickly distinguish between PDUs and match them up easier in the rack, the BlueNet PDUs are available in different colours. Different application or customer areas in the data centre (known as cages) can also be equipped with differently coloured PDUs. 	 Faster differentiation, easier matching of PDUs in the rack Different colours for cages in the data centre Simpler installation, mounting or maintenance
Guarantee Safety of Your Device	Surge Protection Device (SPD)	Type 3 SPD protection modules can be installed with Bachmann PDUs	Increase the level of protection for your sensitive and expensive IT devices

BN0500

Features





Benefits

	BN0500
Measurement:	Current, effective power, frequency, phase angle and energy, measuring accuracy +/- 2%
Display:	Illuminated LCD
Operation:	Local
Extra Benefit:	Energy meter can be reset (value is stored even if there is no power supply)
Optional:	Type 3 surge protection with replaceable arrester module and fault signalling contact

BN0500 with CEE plug | Incl. mounting brackets

D110000 11	idi OLL pidg	mon mounting k	raortoto		
#	C13	C19	CEE 7/3	Outlets in total	Dimensions (W×H×D)
16A/230V 3	.0m H05VV-F 3G 2.5i	mm²			
800.2135	24	4*		28	958x44x47mm
16A/400V 3	.0m H05VV-F 5G 2.5ı	mm²			
800.2403	36	6		42	1616x44x47mm
32A/230V 3	.0m H05VV-F 3G 4m	m²			
800.2407	24	4		28	1086x44x47mm
32A/400V 3	.0m H05VV-F 3G 4m	m²			
800.2410	36	6		42	2042x44x47mm
800.2403		8888 5 888	036 866866 EII		(1) (13) (m)
800.2410	B00000 0000		00000 00000		00000 000000 🖼 🖼

^{*} With integrated IEC lock



Features

- Torsionally rigid profile:
 1U (44mm) ALU profile –
 black or grey,
 profile depth 44mm
- Modular socket design
- Illuminated 2-pole switch
- High-quality electronic components built in e.g. type 3 surge protection, mains and frequency filters
- Micro fuse
- Universal fixing options

- Flexible positioning
- Universal attachment
- Modular platform

19" IT PDU Basic (230 V/50 Hz) | Incl. mounting brackets

• Cable type: 2.0 m H05VV-F 3G 1.50 mm²


• Phase(s): 1

• Nominal voltage: 230V

• Current per phase: 16A

#	16A circuit breaker	Switch	C13	C19	BS1363	Outlets in total	Profile colour
800.3358					7	7	Black
800.3535		•			6	6	Silver
800.3360			9			9	Silver
With Surge	Protection	on					
800.3536					6	6	Silver
800.3537		•			5	5	Silver
With Fuse							
800.3534	•				5	5	Silver





For future orientated, highly efficient power distribution in data centre, server racks and network racks.

Basic 1U Vertical Features

- Torsionally rigid 1 U –
 aluminium profile
- Modular socket design

800.3541

800.3540

- Standard socket colour white; block, yellow, red, brown, blue and green also available
- Optionally with illuminated 2-pole switch
- High-quality electronic components built in e.g. type 3 surge protection, mains and frequency filters

Power distribution units | Incl. mounting brackets

	ioti ibatio		1		.5 .5. 6.6.	.0.0				
#	Cable type H05W-F	Cable length (m)	Plug	Phase(s)	Miniature circuit breaker C16A	C13	C19	BS1363	Outlets in total	Dimensions (W × H × D)
16A/220V/	50 Hz									
800.3539	3G 2.5mm ²	3	CEE	1		16		4	20	735x44x44mm
16A/380V/	50 Hz									
800.0104	5G 2.5mm ²	3	CEE	3		18	3*		21	821x44x44mm
800.3538	5G 2.5mm ²	3	CEE	3				15	15	828x44x44mm
800.3541	5G 2.5mm ²	3	CEE	3		24	6	6	36	1466x44x44mm
32A/220V/	50 Hz									
800.2336	3G 4mm ²	3	CEE	1	2	24	4		28	1119x44x44mm
32A/220V/	50 Hz									
800.3540	5G 4mm ²	3	CEE	3	6	24		6	30	1636x44x44mm
800.3539 800.3538						· 8888	8898 =	l'a		

0000 0000

Accessories:

Plug interlocks

#	
940.103	Locking clips C13, 2-way Red Set for 12 C13 outlets
802.0010	Interlock C13/C19 universal height (6 units)
940.191	SecureSleeve C14 Red 6 units
940.192	SecureSleeve C14 Black 6 units
940.193	SecureSleeve C20 Red 6 units
940.194	SecureSleeve C20 Black 6 units



Locking caps IEC60320 C13 & C19

#	
800.0050	C19 locking caps 10 items incl. unlocking tool
800.0051	C13 locking caps 10 items incl. unlocking tool
800.0052	Unlocking tool for locking cap



Mounting kits for IT PDUs
• The brackets are screwed to the PDU and cap using a screw connection (screws provided)

#	
940.142	Mounting brackets left and right (1U)
940.096	Mounting brackets left and right (>1U)
940.096	Mounting brackets left and right (>1U)



About us

IT power distribution



years of experience

in developing, manufacturing and distributing high-quality power distribution solutions power LIFE.





Over 2,000 standard products





• • •











BlueNet series
BN2000 - BN7500

For more information and place your order, please contact our Sales Team directly!

#wepoweryourlife

Tel: +852 2802 2638

Email: salesap@bachmann.com

www.bachmann.com

